

Smart pressing procedures

Programat®

EP 5010 G2

EP 3010 G2

The next generation
of Programat ceramic
and press furnaces

Making People Smile


<https://stomshop.pro>

The reliable partner for smart pressing procedures

Modern. Intuitive. Smart.
With the objective to meet
the requirements of your
dental laboratory

Proven technologies, such as the fully
automatic press function (FPF), com-
bined with new features - that is what
makes the new Programat press fur-
nace your reliable partner.

The new Programat press furnaces:
EP 5010 G2 and EP 3010 G2



Modern
design

- ✓ Dynamic colour concept
- ✓ Ergonomic shapes and forms
- ✓ Optimized cooling tray for more space and better cooling



High
process
reliability

- ✓ Fast and high-quality firing results due to infrared technology
- ✓ IoT function for free monthly equipment usage reports
- ✓ Optimum integration into the press workflow thanks to preset programs



Intuitive
operation

- ✓ New membrane-sealed keypad with proven colour touchscreen display
- ✓ New user interface featuring new symbols and icons
- ✓ Efficient and reliable performance due to software optimizations



Delivers more than meets the eye.

Stay informed about your furnace. Receive a monthly usage report for your device^[1] free of charge via e-mail.

This is how it works:

1

Make sure the device is connected to your Internet.

2

Register your Programat press furnace on <https://mydevice.ivoclarvivadent.com/>

3

Subscribe to the report^[1]

4

Receive your monthly report^[1] via e-mail

Programat
EP 5010

ivoclar
vivadent

Your advantages of having this service:

- ✓ Documentation on the device utilization rate and performance data, combined with customer-specific recommendations
- ✓ Easy maintenance and planning of repair work to prevent downtimes
- ✓ Continuous quality improvements of your smart device

Infrared technology and fully automatic press function (FPF)

Innovative infrared technology^[2] (IRT) with integrated thermographic camera measures the exact temperature at the surface of the objects being fired and the investment ring. The Programat furnace automatically controls the pre-drying and closing process and adjusts the press process accordingly.

Due to the new patented and fully automatic press function^[3] (FPF), pressing is now even easier and more economical. All you need to do is put the investment ring into the furnace and press the start button - everything else is performed by the furnace itself.

Programat
EP 5010

ivoclar
vivadent

Electronic press drive with force sensor

The electronic press drive with force sensor records and controls the pressure of the press plunger very precisely and therefore ensures top-quality press results. A compressed air connection is not required.

- ✓ Reduced risks of cracks in the ceramic
- ✓ High process reliability thanks to consistent and reproducible high-quality firing results
- ✓ Optimal coordination of the preheating furnace with the press furnace
- ✓ Automatic, fast and convenient selection of the investment ring size

- ✓ Automatic selection of the suitable press program
- ✓ Automatic heating of the press chamber to the appropriate temperature
- ✓ Pressing the fluid ceramic into the investment ring at the right time
- ✓ Controlled post-processing and cooling process

[2] only available with Programat EP 5010 G2
[3] only applicable for Ivoclar Vivadent materials (according to the Instructions for Use)

Further highlights

Crack Detection System (CDS)

The Programat furnace features a Crack Detection System (CDS). This system identifies cracks in the investment ring at an early stage and reduces the pressure, if necessary. As a result, the press process ends in time to protect the restorations.

Convenient loading of the furnace chamber

Upon opening, the furnace head pivots upwards and thus provides ample working space. As a result, the furnace chamber can be loaded easily and comfortably.

Automatic double-range temperature calibration (ATK2)

The ATK2 temperature checking system calibrates the temperature in the furnace fully automatically and accurately in two different temperature ranges. This ensures high-precision press and firing procedures as well as reproducible press and firing results with various types of materials (low- and high-fusing ceramics).

Software update via USB flash drive

It has never been easier to update your software: Simply plug in the USB flash drive containing the latest software version and press the "Software Update" button. The software is being updated automatically.



Save up to 40% of energy!

If the furnace is not being used, simply press the "Power Saving" key to activate the power-saving mode.

Technical data



| Technical data | | |
|--------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Power supply | 110 – 120 V, 50 – 60 Hz 200 – 240 V, 50 – 60 Hz Admissible voltage fluctuations +/- 10 % | |
| Max. power consumption | 12 A at 110 – 120 V 8.5 A at 200 – 240 V | |
| Vacuum pump data | Max. power consumption: 250 W Final vacuum: < 50 mbar Only tested pumps should be used | |
| Dimension of closed furnace | Depth: 465 mm Width: 320 mm / 390 mm (with cooling tray) Height: 550 mm | Depth: 495 mm Width: 320 mm / 395 mm (with cooling tray) Height: 550 mm |
| Dimensions of firing chamber | Diameter: 90 mm Height: 80 mm | |
| Max. firing temperature | 1200 °C | |
| Weight | 18.3 kg | 20.5 kg |
| Safety information | | |
| Radio protection / Electromagnetic compatibility | EMC tested | |
| Delivery form | | |
| | Power cord Vacuum hose Programat firing tray kit 2 Automatic Temperature Checking Set ATK2 (test set) Investment ring cooling grid USB download cable Various accessories | Power cord Vacuum hose Programat firing tray kit 2 Automatic Temperature Checking Set ATK2 (test set) Investment ring cooling grid USB download cable Programat WLAN Kit Various accessories |
| Recommended accessories | | |
| (Not part of the delivery form) | Vacuum pump VP5 Programat Accessory Set Automatic Temperature Checking Set ATK2 | Vacuum pump VP5 Programat Accessory Set Automatic Temperature Checking Set ATK2 Firing tongs |



The right material for your furnace

IPS e.max Press is the original premium lithium disilicate glass-ceramic (LS₂) for the press technique^[4]. It combines accuracy of fit with excellent function and outstanding esthetics as well as high strength (470 MPa)^[5]. The material comes in a wide range of shades and translucency levels for utmost flexibility. With 30 years of experience^[6] in press technology, we help you achieve exceptional efficiency and reliability for your pressing procedures.

At a glance:

- ✓ Impressive esthetics
- ✓ Efficient processing
- ✓ Widest area of application^[7]
- ✓ 10 years guarantee



[4] Schweiger et al. Europäisches Patent 0827941 B1, 1997, Europäisches Patentamt
 [5] Edelhoff D. et al, Clinical performance of occlusal onlays made of lithium disilicate ceramic in patients with severe tooth wear up to 11 years, Dental Materials, 2019, 35, p. 1319-1330
 [6] 30 years of Ivoclar Vivadent press technology
 [7] Studer F., 10 reasons to choose the IPS e.max Press System, Product Presentation, Ivoclar Vivadent, 2020

Product comparison



| | EP 3010 G2 | EP 5010 G2 |
|----------------------------------------------------------------------------|------------|------------|
| Warranty | | |
| Warranty period ^[8] | 2 years | 3 years |
| Hardware equipment | | |
| Colour touchscreen display with membrane-sealed keypad | ✓ | ✓ |
| Electronic press drive with force sensor | ✓ | ✓ |
| QTK2 muffle technology with SiC bottom reflector | ✓ | ✓ |
| OSD with progress indicator | ✓ | ✓ |
| Programat infrared technology (IRT) | | ✓ |
| Software equipment | | |
| Easy operation due to modern control concept | ✓ | ✓ |
| Individual firing/press programs | 300/20 | 500/20 |
| Preset Ivoclar Vivadent firing/press programs | ✓ | ✓ |
| Power Saving Technology | ✓ | ✓ |
| Integrated maintenance and diagnostic programs (e.g. heater, vacuum, etc.) | ✓ | ✓ |
| Fully automatic press function (FPF) | ✓ | ✓ |
| System to bridge short power cuts | ✓ | ✓ |
| Automatic crack detection (CDS) in the investment ring | ✓ | ✓ |
| Software update via USB flash drive | ✓ | ✓ |
| IoT connectivity | ✓ | ✓ |
| Report | ✓ | ✓ |
| Integrated multimedia functions | | ✓ |
| Remote monitoring and diagnostics via Programat app | | ✓ |
| Integrated program copy assistant | | ✓ |
| IRT-controlled pre-drying | | ✓ |
| IRT-controlled recognition of the investment ring size | | ✓ |
| Digital shade assistant (DSA) | | ✓ |
| Temperature calibration | | |
| Automatic double-range temperature calibration (ATK2) | ✓ | ✓ |
| Design and ergonomics | | |
| Integrated holder for firing tongs | ✓ | ✓ |
| Large cooling tray | ✓ | ✓ |
| Ports | | |
| USB ports | 1 | 3 |
| SD card reader | | ✓ |

[8] Consumables excluded

Ivoclar Vivadent AG | Bedererstr. 2 | 9494 Schaan | Liechtenstein
Tel. +423 235 35 35 | Fax +423 235 33 60

ivoclarvivadent.com

<https://stomshop.pro>