We recommend the use of our dublicating silicones, 1:1. Available as:


- 1 kg, component A / B
- 6 kg, component A / B
- 25 kg, component A / B



WaSil soft, 6 kg cask, hardness Shore A: 16-18



WaSil speed, 6 kg cask, hardness Shore A: > 24





Convenient: The containers for the A and B components can be fitted very easy to the unit by the quick couplings, Adapter-sets for various cask sizes are available as accessories



Single-handed operation

#### MADE IN GERMANY

Wassermann is a medium-sized, owner-operated company with head office in Hamburg. We design and produce high-quality technical devices in Germany. Our main users are dental laboratories, dental clinics and various industrial areas worldwide

### Why a Wassermann product?

Wassermann products are manufactured from high-quality materials and the proportion of plastics used is intentionally kept as low as possible. Our devices are known for their suitability for daily use, functionality and longevity. As a result, the users place high levels of trust in the Wassermann brand. We feel it is our duty to support our customers on a daily basis when it comes to safety, service and productivity. Technological perfection, optimum quality and especially

sustainability are the benchmarks we set. Thanks to the combination of these values, the family-owned company, since its establishment in 1927, has gained worldwide recognition as a manufacturer of high-quality products.



Further information are available on our website at www.wassermann.hamburg



/WassermannDentalmaschinen

- Your Dental Dealer

### www.stomshop.pro



### Sidomix II



Wassermann Dental-Maschinen GmbH Rudorffweg 15–17 · 21031 Hamburg · Germany Phone: +49 (0)40 730 926-20/ -24 · Fax: +49 (0)40 730 37 24 export@wassermann-dental.com · www.wassermann.hamburg www.facebook.com/WassermannDentalmaschinen

# Dosing and Mixing Unit

## Sidomix II

High quality construction, made of stainless steel

The **Sidomix II** is a dosing and mixing unit for addition-vulcanizing duplicating silicones of low viscosity. A regulable bypass circuit ensures an optimum mixing ratio. The mixing ratio can be adjusted very easyly and quickly by the user with the help of a convenient quantity flow control. The desired components are mixed 1:1 and dosed correctly – automatically, totally homogenous and fully bubble-free.



The mixing head with separate outlets makes mixing of components impossible – even when attaching and removing the mixing cannulas

Material and time saving with loss-free filling of several flasks with one mixing cannula

#### **Major Features**

#### • Included in delivery:

Set material cask with quick fitting coupling, 2 x 2 liter Mixing canulas, pink, 10 pcs.

Accessories	Item no.
Set material cask with quick fitting coupling, 2 x 2 liter	172640
Stand small for dublicating silicones, 2 x 6 kg-cask	172631
Stand tall for dublicating silicones, 2 x 25 kg-cask	172632
Connecting tubes cpl., 2 pcs.	172633
Adapter-set for dublicating silicones, 2 x 1 kg-cask	172634
Adapter-set for dublicating silicones, 2 x 6 kg-cask	172636
Mixing canulas 1:1, inner Ø 5.4 mm, pink, 100 pieces	622002
Consumable materials Dublicating silicone, 1:1	
WaSil soft, hardness Shore A: 16-18, 2 x 1 kg, component A / B	656060
WaSil soft, hardness Shore A: 16-18, 2 x 6 kg , component A / B	656061
WaSil soft, hardness Shore A: 16-18, 2 x 25 kg, component A / B	656062
WaSil speed, hardness Shore A: > 24, 2 x 1 kg, component A / B	656070
WaSil speed, hardness Shore A: $> 24$ , 2 x 6 kg , component A / B	656071
WaSil speed, hardness Shore A: > 24, 2 x 25 kg, component A / B	656072

Sidomix II	Item no. 172980
Voltage	220-240 V / 50/60 Hz
Power consumption	1.6 A
Output	260 W
W x H x D max. W x H x D (housing)	275 x 340 x 440 mm 242 x 305 x 360 mm
Weight	242 x 305 x 360 mm
Gewicht	11.5 kg
Sound level	≤ 70 dB (A)